

Completion of this form, and providing us with highlighted drawings, has proven to greatly reduce our turn-around time on quotation requests. **Your assistance is greatly appreciated.**

Request Date: \_\_\_\_\_  
 Company Name: \_\_\_\_\_  
 Email: \_\_\_\_\_  
 Project Name: \_\_\_\_\_  
 Specifier: \_\_\_\_\_

Quotation Due Date: \_\_\_\_\_  
 Contact Name: \_\_\_\_\_  
 Phone: \_\_\_\_\_  
 Project Location: \_\_\_\_\_  
 Date Req'd on Site: \_\_\_\_\_



PanelGrip® Standard



PanelGrip® Narrow

Approx. Footage: \_\_\_\_\_

**Glass Thickness Range:**

Shoe Length: 10ft 20ft

.496" - .550"

PanelGrip® Style: Standard Narrow

.569" - .638"

Glass Type: Monolithic Laminate

.624" - .726"

Pre-drilled Countersunk Holes: Yes No

.719" - .781"

Mounting Surface: Steel Concrete

.768" - .874"

Cladding: Yes No Length: 10ft

Type: Satin Aluminum Black Aluminum Satin Stainless  
 Satin Anodized Aluminum Polished Stainless

End Caps: Yes No Number of End Caps: \_\_\_\_\_

Gasket: With Cladding Without Cladding

Cap Rail: 304 Stainless Steel Slotted 316 Stainless Steel Slotted  
 304 Stainless Steel Oval Formed Extruded Aluminum, 900 lb/ft  
 304 Stainless Steel Roll Formed Brass Roll Formed

Finish Type: Mill Satin Longitudinal Satin  
 Polished Satin Anodized (Aluminum rail only)



@wagnercompanies

## Aluminum Extruded Shoe

Choose one, follow column down

		GR2460HCB GR2460HCB-10	GR2457HCB GR2457HCB-10	
Isolators Choose one matching shoe	1/2" Monolithic .469" to .531"	PG2460 Brown Isolator White .090" Pad	PG2472 Black Isolator Black .160" Pad	
	9/16" Laminate .496" to .550"	PG2460 Brown Isolator White .090" Pad	PG2472 Black Isolator Black .160" Pad	
	15mm Laminate .569" to .638"	N/A	PG2415 Dk. Grey Isolator White .090"/.125" Pad	
	17mm Laminate .642" to .726"	N/A	PG2417 Lt. Grey Isolator White .090"/.125" Pad	
	3/4" Monolithic .719" to .781"	N/A	PG2475 White Isolator White .090"/.125" Pad	
	21 mm Laminate .768" to .874"	N/A	PG2421 Cream Isolator Red .035" Pad	
Mounting Hardware Choose one matching shoe	Concrete	Self-Tapping Anchor	3/8" by 4" *	KHEZ500-0450 1/2" by 4 1/2"
		Expansion Anchor	3/8" by 4" *	1/2" by 5-1/8" *
	Steel (1/2" min)	Zinc Plated Steel Cap Screw	SHC1Z1216-0750 3/8"-16 by 3/4"	SHC1Z1213-0750 1/2"-13 by 3/4"
		Stainless Steel Cap Screw	SHC1Z1216-0750 3/8"-16 by 3/4"	SHC1Z1213-0750 1/2"-13 by 3/4"
End Caps Choose one matching shoe	With Cladding	Stain Aluminum	GR2852EC.4	GR2876EC.4
		Satin Anodized Al	GR2852EC.4AN	GR2876EC.4AN
		Stain Stainless	GR3852EC.4	GR3876EC.4
		Polished Stainless	GR3852EC.7	GR3876EC.7
	Without Cladding	Polished Brass	GR4852EC.7	GR4876EC.7
		Stain Aluminum	GR2852E.4	GR2876E.4
		Satin Anodized Al	GR2852E.4AN	N/A
		Stain Stainless	GR3852E.4	GR3876E.4
		Polished Stainless	GR3852E.7	GR3876E.7
		Polished Brass	GR4852E.7	GR4876E.7

\*Recommended to purchase through Hilti



@wagnercompanies

<b>Aluminum Extruded Shoe</b> Choose one, follow column down		GR2460HCB GR2460HCB-10	GR2457HCB GR2457HCB-10
<b>Cladding</b> Choose one	Anodized Aluminum	GR2802.4AN	GR2802.4AN
	Satin Stainless Steel	GR3802.4	GR3802.4
	Polished Stainless Steel	GR3802.7	GR3802.7
	Polished Brass	GR4802.7	GR4802.7
	Tape	GR975	GR975

<b>Works With Both Shoes</b>		With Cladding	Without Cladding
<b>Gaskets</b> Choose one	20' Length Cap Rail GR9397-20	GR9302-20	GR9355-20
	40' Length Cap Rail GR9397-40	GR9302-40	GR9355-40
	100' Length Cap Rail GR9397-100	GR9302-100	GR9355-100
	250' Length Cap Rail GR9397	N/A	GR9355
	500' Length Cap Rail N/A	GR9302	N/A