

Completion of this form, and providing us with highlighted drawings, has proven to greatly reduce our turn-around time on quotation requests. **Your assistance is greatly appreciated.**

Request Date: _____

Quotation Due Date: _____

Company Name: _____

Contact Name: _____

Email: _____


Phone: _____

Project Name: _____

Project Location: _____

Specifier: _____

Date Req'd on Site: _____



PanelGrip® Standard



PanelGrip® Narrow

Approx. Footage: _____

Glass Thickness Range:

Shoe Length: 10ft 20ft

.496" - .550"

PanelGrip® Style: Standard Narrow

.569" - .638"

Glass Type: Monolithic Laminate

.624" - .726"

Pre-drilled Countersunk Holes: Yes No

.719" - .781"

.768" - .874"

Mounting Surface: Steel Concrete

ICC-ES Compliant: Yes No

Cladding: Yes No Length: 10ft

Type: Satin Aluminum Black Aluminum Satin Stainless

Satin Anodized Aluminum Polished Stainless

End Caps: Yes No Number of End Caps: _____

Gasket: With Cladding Without Cladding

Cap Rail: 304 Stainless Steel Slotted 316 Stainless Steel Slotted

304 Stainless Steel Oval Formed Extruded Aluminum, 900 lb/ft

304 Stainless Steel Roll Formed Brass Roll Formed

Finish Type: Mill Satin Longitudinal Satin

Polished Satin Anodized (Aluminum rail only)

 @wagnercompanies



If ICC-ES compliance needed, please contact rfq@mailwagner.com.

Isolators Choose one matching shoe	Aluminum Extruded Shoe Choose one, follow column down		<input type="checkbox"/> GR2460HCB <input type="checkbox"/> GR2460HCB-10	<input type="checkbox"/> GR2457HCB <input type="checkbox"/> GR2457HCB-10
	1/2" Monolithic .469" to .531"	<input type="checkbox"/>	PG2460 Brown Isolator White .090" Pad	<input type="checkbox"/> PG2472 Black Isolator Black .160" Pad
	9/16" Laminate .496" to .550"	<input type="checkbox"/>	PG2460 Brown Isolator White .090" Pad	<input type="checkbox"/> PG2472 Black Isolator Black .160" Pad
	15mm Laminate .569" to .638"	<input type="checkbox"/>	N/A	<input type="checkbox"/> PG2415 Dk. Grey Isolator White .090"/.125" Pad
	17mm Laminate .642" to .726"	<input type="checkbox"/>	N/A	<input type="checkbox"/> PG2417 Lt. Grey Isolator White .090"/.125" Pad
	3/4" Monolithic .719" to .781"	<input type="checkbox"/>	N/A	<input type="checkbox"/> PG2475 White Isolator White .090"/.125" Pad
	21 mm Laminate .768" to .874"	<input type="checkbox"/>	N/A	<input type="checkbox"/> PG2421 Cream Isolator Red .035" Pad
Mounting Hardware Choose one matching shoe	Concrete	Self-Tapping Anchor	<input type="checkbox"/> WB7216 3/8" by 4"	<input type="checkbox"/> KHEZ500-0450 1/2" by 4 1/2"
		Expansion Anchor	<input type="checkbox"/> 3/8" by 4" *	<input type="checkbox"/> HSL3M1040 1/2" by 5 1/8"
	Steel (1/2" min)	Zinc Plated Steel Cap Screw	<input type="checkbox"/> SHC1Z3816-0750 3/8"-16 by 3/4"	<input type="checkbox"/> SHC1Z1213-0750 1/2"-13 by 3/4"
		Stainless Steel Cap Screw	<input type="checkbox"/> SHC1Z3816-0750 3/8"-16 by 3/4"	<input type="checkbox"/> SHC1Z1213-0750 1/2"-13 by 3/4"
End Caps Choose one matching shoe	With Cladding	Stain Aluminum	<input type="checkbox"/> GR2852EC.4	<input type="checkbox"/> GR2876EC.4
		Satin Anodized Al	<input type="checkbox"/> GR2852EC.4AN	<input type="checkbox"/> GR2876EC.4AN
		Stain Stainless	<input type="checkbox"/> GR3852EC.4	<input type="checkbox"/> GR3876EC.4
		Polished Stainless	<input type="checkbox"/> GR3852EC.7	<input type="checkbox"/> GR3876EC.7
	Without Cladding	Stain Aluminum	<input type="checkbox"/> GR2852E.4	<input type="checkbox"/> GR2876E.4
		Satin Anodized Al	<input type="checkbox"/> GR2852E.4AN	<input type="checkbox"/> N/A
		Stain Stainless	<input type="checkbox"/> GR3852E.4	<input type="checkbox"/> GR3876E.4
		Polished Stainless	<input type="checkbox"/> GR3852E.7	<input type="checkbox"/> GR3876E.7

*Recommended to purchase through Hilti

Aluminum Extruded Shoe		<input type="checkbox"/>	GR2460HCB GR2460HCB-10	<input type="checkbox"/>	GR2457HCB GR2457HCB-10
Cladding Choose one	Anodized Aluminum	<input type="checkbox"/>	GR2802.4AN	<input type="checkbox"/>	GR2802.4AN
	Satin Stainless Steel	<input type="checkbox"/>	GR3802.4	<input type="checkbox"/>	GR3802.4
	Polished Stainless Steel	<input type="checkbox"/>	GR3802.7	<input type="checkbox"/>	GR3802.7
	Tape	<input type="checkbox"/>	GR975	<input type="checkbox"/>	GR975

Works With Both Shoes		With Cladding		Without Cladding	
Gaskets Choose one	20' Length Cap Rail GR9397-20	<input type="checkbox"/>	GR9302-20	<input type="checkbox"/>	GR9355-20
	40' Length Cap Rail GR9397-40	<input type="checkbox"/>	GR9302-40	<input type="checkbox"/>	GR9355-40
	100' Length Cap Rail GR9397-100	<input type="checkbox"/>	GR9302-100	<input type="checkbox"/>	GR9355-100
	250' Length Cap Rail GR9397	<input type="checkbox"/>	N/A	<input type="checkbox"/>	GR9355
	500' Length Cap Rail N/A	<input type="checkbox"/>	GR9302	<input type="checkbox"/>	N/A