

PanelGrip® How To Buy Guide

Completion of this form, and providing us with highlighted drawings, has proven to greatly reduce our turn-around time on quotation requests. Your assistance is greatly appreciated.

Quotation Due Date:
Contact Name:
Phone:
Project Location:
Date Req'd on Site:



PanelGrip® Standard



PanelGrip® Narrow

Approx. Footage:	Glass Thickness Range:
Approx. rootage.	oluss fillokiless kullye.

Shoe Length: 10ft 20ft .496" - .550"

.569" - .638" PanelGrip® Style: Standard Narrow .624" - .726"

Glass Type: Monolithic Laminate .719" - .781" **Pre-drilled Countersunk Holes:** Yes No .768" - .874"

ICC-ES Compliant: Mounting Surface: No Steel Concrete Yes

Cladding: Yes No Length: 10ft

Type: Satin Aluminum **Black Aluminum** Satin Stainless

> Satin Anodized Aluminum Polished Stainless

Number of End Caps: ____ End Caps: Yes No

Gasket: With Cladding Without Cladding

Cap Rail: 304 Stainless Steel Slotted 316 Stainless Steel Slotted

> 304 Stainless Steel Oval Formed Extruded Aluminum, 900 lb/ft

304 Stainless Steel Roll Formed **Brass Roll Formed**

Finish Type: Mill **Longitudinal Satin** Satin

> Polished Satin Anodized (Aluminum rail only)













PanelGrip® How To Buy SKU

If ICC-ES compliance needed, please contact rfq@mailwagner.com.

Aluminum Extruded Shoe Choose one, follow column down			GR2460HCB GR2460HCB-10	GR2457HCB GR2457HCB-10
Isolators Choose one matching shoe	1/2" Monolithic .469" to .531"		PG2460 Brown Isolator White .090" Pad	PG2472 Black Isolator Black .160" Pad
	9/16" Laminate .496" to .550"		PG2460 Brown Isolator White .090" Pad	PG2472 Black Isolator Black .160" Pad
	15mm Laminate .569" to .638"		N/A	PG2415 Dk. Grey Isolator White .090"/.125" Pad
	17mm Laminate .642" to .726"		N/A	PG2417 Lt Grey Isolator White .090″/.125″ Pad
	3/4″ Monolithic .719″ to .781″		N/A	PG2475 White Isolator White .090"/.125" Pad
	21 mm Laminate .768" to .874"		N/A	PG2421 Cream Isolator Red .035" Pad
Mounting Hardware Choose one matching shoe	Concrete	Self-Tapping Anchor	3/8" by 4" *	KHEZ500-0450 1/2" by 4 1/2"
	Con	Expansion Anchor	3/8" by 4" *	1/2" by 5-1/8" *
	Steel (1/2" min)	Zinc Plated Steel Cap Screw	SHC1Z1216-0750 3/8"-16 by 3/4"	SHC1Z1213-0750 1/2"-13 by 3/4"
	Steel (1	Stainless Steel Cap Screw	SHC1Z1216-0750 3/8"-16 by 3/4"	SHC1Z1213-0750 1/2"-13 by 3/4"
		Stain Aluminum	GR2852EC.4	GR2876EC.4
Ф	Cladding	Satin Anodized Al	GR2852EC.4AN	GR2876EC.4AN
End Caps Choose one matching shoe	With Cl	Stain Stainless	GR3852EC.4	GR3876EC.4
		Polished Stainless	GR3852EC.7	GR3876EC.7
	бL	Polished Brass	GR4852EC.7	GR4876EC.7
	Sladdir	Stain Aluminum	GR2852E.4	GR2876E.4
	Without Cladding	Satin Anodized Al	GR2852E.4AN	N/A
	W	Stain Stainless	GR3852E.4	GR3876E.4
		Polished Stainless	GR3852E.7	GR3876E.7
		Polished Brass	GR4852E.7	GR4852E.7

*Recommended to purchase through Hilti

@wagnercompanies



(in (f) (2) (ii)





Aluminum Extruded Shoe Choose one, follow column down		GR2460HCB GR2460HCB-10	GR2457HCB GR2457HCB-10
Cladding Choose one	Anodized Aluminum	GR2802.4AN	GR2802.4AN
	Satin Stainless Steel	GR3802.4	GR3802.4
	Polished Stainless Steel	GR3802.7	GR3802.7
	Polished Brass	GR4802.7	GR4802.7
	Tape	GR975	GR975

Works With Both Shoes		With Cladding	Without Clado	ling
	20′ Length Cap Rail GR9397-20	GR9302-20	GR9355-20	
Gaskets Choose one	40' Length Cap Rail GR9397-40	GR9302-40	GR9355-40	
	100' Length Cap Rail GR9397-100	GR9302-100	GR9355-100	
	250' Length Cap Rail GR9397	N/A	GR9355	
	500' Length Cap Rail N/A	GR9302	N/A	







